



DIMENSION	MEASURE		DIMENSION	MEASURE	
APPLIANCE					
Product width	730	mm	MAX worktop thickness with oven	0	mm
Product depth	510	mm	Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"	No	
Radius of product corner	6	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"	No	
Product height (MAX protrusion from the worktop)	60	mm	Indicates the position of the opening in the back side of the cabinet with oven	N/A	
Underneath the bearing area of the appliance	42	mm	MIN Width of rear opening required with oven	0	mm
Distance between cut out and top frontal projection	15	mm	MIN Depth of rear opening required with oven.	0	mm
Distance between cut out and top lateral projection	85	mm	MIN AREA of rear opening required with oven	0	cm ²
Plateau thickness	7	mm	MIN distance from cabinet to rear wall, with oven	0	mm
Gas outlet positioning	Rear right		Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N"	No	
Gas outlet X positioning	112	mm	MIN Frontal gap required, with oven (2)	0	mm
Gas outlet Y positioning	25	mm	MIN frontal opening area required with oven	0	cm ²
Power cable	With product		WITH CABINET		
Power cable positioning	Rear		MIN worktop thickness with cabinet	0	mm
CUT OUT			MAX worktop thickness with cabinet	0	mm
MIN front distance from cut-out to end worktop	0	mm	Indicates whether a protection tray against heat or contact is needed. Default is "Y"	Yes	
MIN rear distance from cut out to wall/furniture	55	mm	MIN distance from bottom line of appliance to protection tray	20	mm
MIN lateral distance from cut out to wall/furniture	185	mm	Indicates whether a ventilation opening in the tray is needed or not with cabinet	No	
MIN height from worktop to above furniture	420	mm	Recess dimension X	0	mm
MIN cut out width	560	mm	Recess dimension Y	0	mm
MAX cut out width	562	mm	Positioning dimension X by axis	0	mm
MIN cut out depth	480	mm	Distance of the tray from the back panel/wall	0	mm
MAX cut out depth	482	mm	Indicates whether a divider is available	N/A	
MIN cut out radius	0	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"	No	
MAX cut out radius	8	mm	Indicates the position of the opening in the back side of the cabinet.	N/A	
FLUSH INSTALLATION			MIN Width of rear opening of the cabinet	0	mm
Indicates whether a flush installation is possible. Default is "N"	Yes		MIN Depth of rear opening of the cabinet	0	mm
MIN Milling rabbet width	733	mm	MIN AREA of rear opening of the cabinet	0	cm ²
MAX Milling rabbet width	735	mm	MIN distance from cabinet to rear wall	0	mm
MIN Milling rabbet depth	513	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"	No	
MAX Milling rabbet depth	515	mm	MIN Frontal gap of the cabinet	0	mm
Milling rabbet thickness	12	mm	MIN frontal opening area of the cabinet	0	cm ²
Radius milling rabbet	6.5	mm	INSTALLATION SPACE		
Flush installation KIT (2)	With product		Depth of immersion underneath the appliance	10	mm
Indicates the minum worktop thickness with standard installation for gas	20	mm	Width protruding area below bottom box	61	mm
Indicates the maximum worktop thickness with standard installation for gas	60	mm	Depth protruding area below bottom box	62	mm
Indicates the minum worktop thickness with flush installation for gas	30	mm	Protruding area: X positioning	74	mm
Indicates the maximum worktop thickness with flush installation for gas	68	mm	Protruding area: Y positioning	9	mm
WITH OVEN			ACCESSORIES FOR INSTALLATION		
Indicates whether the cooktop can be installed above oven. Default is "Y"	Yes		Gasket	Separate	
MIN worktop thickness with oven	0	mm			

DIMENSION	MEASURE	
	KIT	
Clips	Separate KIT	
Injector KIT	Separate KIT	
Elbow KIT	N/A	
COOKTOP HOOD INSTALLATION ONLY FOR GAS		
MIN distance from cooktop to above furniture	700	mm
MIN distance between cabinets above the cooktop	600	mm
MAX distance between cabinets above the cooktop	750	mm